



The Acoustic Ones



Special Boosters

Special boosters 35 kHz/20 kHz

The special boosters are suitable for the amplification of the amplitude in special applications.



- Suitable for special applications of various kinds
- The ideal booster for every application thanks to a great diversity of amplification factors and materials
- Heavy duty
- Low-loss and true to amplitude



Specification special boosters

Operating frequency:	20 kHz / 35 kHz		
Weight:	Booster 20 kHz:	1.5 kg	
	Booster 35 kHz:	350 g	
Housing:	Booster 20 kHz:	Nickel-plated steel, without shoulder	
	Booster 35 kHz:	Nickel-plated steel, booster with thread for height adjustment	
Amplification factors:	Booster 20 kHz without shoulder:	Aluminium:	1:1 / 1:1.5
	Booster 20 kHz with shoulder elastic:	Aluminium:	1:1 / 1:1.5
		Titanium:	1:2
	Booster 35 kHz with thread:	Aluminium:	1:1 / 1:1.5
		Titanium:	1:2 / 1:2.5 / 1:3
	Booster 35 kHz with thread elastic:	Aluminium:	1:1.5
		Titanium:	1:2

Additional technical information available on request.



RINCO ULTRASONICS AG
 CH-8590 Romanshorn 1
 Tel. +41 71 466 41 00
 Fax +41 71 466 41 01
 info@rincoultrasonics.com
 www.rincoultrasonics.com