



The Acoustic Ones



Standard Converters

Standard converters 70 kHz / 35 kHz / 20 kHz

The standard converters are suitable for the operation in standard machines and special actuators.



- Designed for integration into ultrasonic welding machines and special purpose machines
- The ideal converter for every application thanks to a wide range
- Heavy duty



Specification standard converters

| | | |
|----------------------|--|---------------|
| Operating frequency: | C70-2: | 70 kHz |
| | C35-10/C35-11/C35-12/C35-13: | 35 kHz |
| | C20-10/C20-12: | 20 kHz |
| Weight: | C70-2: | 100 g |
| | C35-10/C35-11/C35-12/C35-13: | 300 g |
| | C20-10/C20-12: | 1.5 kg |
| Generator: | Suitable for all types of the relevant frequency | |
| Housing: | C70-2: Closed steel housing C35-10/C35-11: Closed steel housing C35-12/C35-13: Open steel housing C20-10: Closed steel housing C20-12: Open steel housing | |
| Maximum temperature: | 50° C If used in continuous operation or with high temperatures, then air cooling should be used. | |

Additional technical information available on request.



RINCO ULTRASONICS AG
 CH-8590 Romanshorn 1
 Tel. +41 71 466 41 00
 Fax +41 71 466 41 01
 info@rincoultrasonics.com
 www.rincoultrasonics.com